

BITUKOTE[®]

PRODUCT DATA SHEET

BITUKOTE[®] BITUMEN PAINT (EMULSION)

SCOPE

BITUKOTE BITUMEN PAINT (EMULSION) is produced with selected high quality bitumen and is viscous, nonflammable and non-toxic. The Bitukote Bitumen Paint (Emulsion) can be mixed with cement, sand and other filling materials. Bitukote Bitumen Paint (Emulsion) has excellent waterproofing and protecting properties in all weathers. In its applied dry status it does not run or drip in high temperature conditions.

USES

Concrete and masonry from attack by sulphates, chlorides and moisture.

CHARACTERISTICS

Appearance	:	Dark - brown dries to black
Specific gravity	:	Approx. 0.9 Kg/Litre
Residue by evaporation	:	50 +/- 5%
Flammability	:	No indication of ignition or fire
Firm test	:	Attained in 24 hours
Heat test (+65°C)	:	No sag, flow or blistering
Theoretical spread rate	:	2 - 6 M ² /Litre depending on porosity
Drying time	:	Depends on application rate and climatic conditions, approximately 2 - 5 hours

STORAGE & HANDLING

In sealed container away from direct sunlight not less than one year.

SURFACE PREPARATION

Ensure the surface is clean, dry or slightly damp, free from oil, grease, dust and other contaminants.

APPLICATION METHOD

Apply two coats allowing first coat to dry before applying second coat. Do not apply when the surface temperature is below 5°C. Bitukote Bitumen Paint (Emulsion) can be applied by brush, roller or airless spray.

CLEANING

Clean tools with water in wet state, with white spirit or turpentine substitute if dry.

GENERAL INFORMATION

The information provided on this data sheet is not intended to be complete and is provided as general advice only. It is the responsibility of the user to ensure the product is suitable for the purpose for which he wishes to use it. The manufacturer reserves the right to change the above specifications without notice.

Technical consultancy is always available to ensure optimum specification and performance.

Manufactured by:-



Gulf Membrane & Coating Industries W.L.L.

Post Box 10266

State of Bahrain

Tel.: 770019 Fax : 774450